







The Simple SELEKTA spreading discs with moveable spreading vanes provide a precise spread pattern. The setting scale allows the spreading vanes to be accurately set. The wide, flat trajectory spread pattern is insensitive to both side wind and varying fertiliser densities.









The oil-immersed gearbox is built at the heart of the Junior twin disc spreaders. Double sealed, and with shear bolt overload protection on the 540rpm PTO drive, Junior gearboxes are well proven and are maintenance-free.

The spread rate adjustment with its shutter slides is located well out of the 'dirty area' meaning that it is not splashed by the tractor wheels or with fertiliser dust from the spreading discs. This means that the machine stays clean and easy to operate. The spreading shutters are opened and closed either by the manual control lever or the hydraulic ram.







The shape of the hopper ensures that the fertiliser is gently and evenly delivered to the shutter apertures, this has the added advantage that the hopper is virtually completely emptied so there is next to no fertiliser wasted when cleaning the machine out.

The super low filling height means that the Junior 600 and 800 can be directly loading from a tipping trailer or from a bulk hopper.



The galvanised in hopper grid is useful when filling with bulk stored fertilisers, as any stones or lumps are stopped from blocking the apertures.

The hopper cover is a standard feature to keep the machine and the fertiliser clean and free from other material.





A very robust and compact design giving excellent reliability and value – from the range of MTL Machinery Brand products





Strathpeffer Road, Dingwall IV15 9QF

Tel: 01349 867521 Parts Hotline Tel: 01349 867210

E: sales@mclarentractors.co.uk

Visit our website for details on current stock: www.mclarentractors.co.uk